

## MD 214 PEDESTRIAN I2V DEPLOYMENT

Warren Henry P.E., PTOE Asst. Division Chief, Mobility Planning & Engineering Division (MPED) Office of Transportation Mobility & Operations (OTMO) MDOT State Highway Administration WHenry@mdot.maryland.gov



# DEFINING "I2V"

- I2V = Infrastructure-to-Vehicle
- Reserved for connected vehicle communications
- Part of the broader connected & automated vehicle ecosystem
- Exchanges information in realtime from infrastructure to technology embedded inside a vehicle





### EXAMPLE OF A CONNECTED ECOSYSTEM



### DEFINING: DSRC & C-V2X

#### DSRC

Dedicated Short Range Communication

A radio wave that transmits data directly from one point to another at a very low latency (e.g. 10 times per second) C-V2X (existing networks) Cellular - Vehicle to Everything

Similar to DSRC, the data is expected to transmit directly from one point to another; however, most of the technology is still not proven at scale.







# MD 214: PROJECT DETAILS

#### Location

• MD 214 (Central Avenue) @ Addison Road

#### Funding

Project is a 2019 State Transportation Innovation Council (STIC) grant award.

#### Technology

- Siemens dual mode roadside unit (RSU): DSRC and C-V2X capabilities.
- Bosch cameras for detection.
- ISS security credentialing for message exchanges.

#### Goals

- Pilot new technology for longer term standards development and staff upskilling.
- Deploy a dual mode DSRC/C-V2X radio for crosswalk safety.
- Identify barriers to the project delivery as it relates to connected vehicle technologies.
- Incentivize private industry to pursue connected vehicle technologies.
- Demonstrate Maryland is a player in the connected vehicle arena.



# POINTS OF CLARIFICATION

### Project Does <u>NOT</u>...

'Track' or record people in the crosswalk.

#### Act in place of the existing signal pedestrian crossing operations.

- Pedestrians crossing will continue to cross or request to cross normally.
- The signal will <u>NOT</u> change based on this connected vehicle application.

#### Force cars to stop.

- It is still the responsibility of a driver receiving these notifications to act.
- Maryland law still applies, and this project does not change those laws!



### PROJECT TIMELINE

- Fall 2019: Project idea submitted to STIC and funding awarded.
- **Spring 2020**: Invitation for bid released for vendor selection.
- Fall 2020: Project kick off after several month of procurement processes.
- **Winter 2021**: Submitted license requests to the FCC and received the experimental C-V2X license within 2 weeks, but no approval for the DSRC license.

#### Spring 2021:

- Installation of the RSU and sensors go up.
- Troubleshoot for 2-3 weeks as the system failed to message out.
- Error found (defective RSU) and CV2X activated.
- FCC approves DSRC license after several months' wait.
- DSRC activated as a dual mode in parallel to the CV2X.

#### Summer 2021:

• Testing of the RSU messaging and sensors.

#### December 2021:

• Final Report.



## PROJECT COST BREAKDOWN (ROUNDED)

Item	Cost
Vendor (RSU, sensors, system + maintenance for 12 months, and install staff time)	\$50,000
MDOT SHA project management and installation staff time	\$20,000
MDOT SHA Engineering Design	\$7,500
MDOT SHA Offices review, approval, and install (mixed staff and consultant support)	\$6,500
Total rounded cost	\$74,000





### PROJECT LOCATION

- Prince George's County, Maryland
- MD 214 at Addison
  Road Seat Pleasant
  Metro Station
- One intersection only



# LOCATION SELECTION PROCESS

- Prince George's County has a high rank in pedestrian severity and crash rate
- Simple intersection design
- Intersection signal infrastructure is fairly new
  - > New mast arms & poles with low weight (i.e. can support additional sensors)
  - Communication and power connections available
  - > New signal cabinet met space needs for this type of deployment
  - History of crash & recommended mitigation: no signal (prior to 2017), signal (2017/2019), DSRC/CV2X (2021+)



## INFRASTRUCTURE LAYOUT





## **DETECTION & NOTIFICATION**

PSM

SPAT/MAP



- Camera/Sensor Detector to track the pedestrian
- Detector provides pedestrian location, speed and heading to RSU
- RSU creates PSM or TIM and broadcast to the OBUs
- OBU calculate collision trajectory and warns the driver



© Siemens Mobility, Inc. 2019



## TECHNICAL SETUP



## WHAT DOES IT LOOK LIKE?





ADMINISTRATION

# POTENTIAL VENDORS

#### Sensor Vendors:

- Miovision
- Gridsmart
- Iteris
- Continental
- Mobileye
- Bosch
- FLIR Systems
- DENSO Corporation
- Aptiv PLC
- Panasonic
- Derq
- Alpine

#### **RSU Vendors & Deployers:**

- Econolite
- Cohda Wireless
- Lear Systems
- Kapsch Group
- Norbit Group
- Siemens
- Danlaw
- Commsignia
- DENSO
- WaveMobile
- TraffiCast

#### Other Deployment:

Consultants



### SECURITY CREDENTIAL MANAGEMENT SYSTEM (SCMS) FOR CYBERSECURITY

The SCMS provides the mechanism for V2X devices to exchange information in a trustworthy and privacy-protective manner using digital certificates.

#### **SCMS Benefits**

- **Ensures integrity** users can trust that the message was not modified between sender and receiver
- **Ensures authenticity** users can trust that the message originates from a trustworthy and legitimate source
- **Ensures privacy** users can trust that the message appropriately protects their privacy
- Helps achieve interoperability different vehicle makes and models will be able to talk to each other and exchange trusted data without pre-existing agreements or altering vehicle designs

#### https://www.ghsiss.com/v2x/marylanddot/



### HOW FAR DO PSM REACH?



#### Legend



- RSU Location (approximately 23 feet high)
- PSM received without package loss

PSM occasionally received, frequent package loss and complete loss before this section



# LESSON LEARNED: BID & COST

- The cost of the vendor to provide the RSU and installation staff time was higher than anticipated and the miscellaneous costs tallied up to the aforementioned total (\$74,000).
- As a first-time deployment MDOT SHA staff had to upskill, however future costs are expected to be lower.
- The invitation for bid was successful in attracting companies to notice that Maryland was "engaged" in the CV field.



# LESSONS LEARNED:

- Installation through MDOT SHA resources helped staff learn how to install RSUs.
- Installation of the Bosch camera sensors was not difficult, as staff frequently installs cameras for traffic incident management.
- Software tuning and message verification were done almost entirely through the vendor.
- Internal staff upskilling, apart from knowing how to remote into the cameras and the RSU, are still limited.





# LESSONS LEARNED: TESTING

- Requiring that all OBUs be registered over the Maryland SCMS limits the rate of deployment.
- Original Equipment Manufacturers (OEMs) have not mass scaled invehicle units, nor registered them in SCMS, meaning it is unlikely they will be providing in-vehicle notifications to the public any time soon.
- This severely hampers an IOOs ability to improve safety through CV technologies.





#### Show only these records: TX WSA C TX Traffic TX Drop C Details

		ar   Y Filter						
		DI BOUT (FLHIN)						
		D:S007(PLAIN)						
		D:8007(PLAIN)						
		D:8007(PLAIN)						
		D: S007(PLAIN)						
		D:8007(PLAIN)						
		D:8007(PLAIN)						
		D:8007(PLAIN)						
		D:8007(PLAIN)						
		D: 8007 (PLAIN)						
		D:8007(PLAIN)						
		D:S007(PLAIN)						
		D:8007(PLAIN)						
		D:8007(PLAIN)						
		0:8007(PLAIN)						
		D:8007(PLAIN)						
		D:S007(PLAIN)						
		D: 8007 (PLAIN)						
		D:8007(PLAIN)						
		D:27(SIGNED)					ate=6000 T	ID+3
		D:27(SIGNED)						
16:33:59.673	8D:SCH4 PS1	D:8007(PLAIN)	80211	JOILT.	Len+126/11	\$ Pou=46	Rate=6000	TZD-
		ID:27(SIGNED)					ate=6000 T	ID=3
		D:27(SIGNED)						
		D:27(SIGNED)					ate=6000 T	ID=3
		D:27(SIGNED)						
		D:8007(PLAIN)						
		D:27(SIGNED)					ate=6000 T	10+7
		D:27(SIGNED)						
		D:27(SIGNED)					ate=6000 T	ID=3
		D:27(SIGNED)						
		D: S007(PLAIN)						
		D:8007(PLAIN)						
		D:27(SIGNED)					ate-6000 T	ID=3
16-14-01 014	an-crus pc	0-27/STGHED)	DO'E VIE	T LA	0=770/20 Th	Dell		

tow only these records: 🗇 TX WSA 🛋 TX Traffic 🗇 TX Drop 🗇 Detai

		Clear   🍸 Filter logs   📑 Copy to clipboard
		#JID.1/(JIGHCO) BOIII ANIT CEN+1/F/IF FORMAG HECE+0000 (10+)
		PSID:27(SIGNED) PCS XMIT Len=279/29 TID=8
		PSID:27(SIGNED) 80211 XHIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XHIT Len+279/29 TID+8
		PSID:8007(PLAIN) 80211 X01T Len=126/118 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) 80211 XHIT Let=279/29 Pou=46 Rate=6000 TID=3
		PSID:27(SIGNED) PCS XMIT Len=279/29 TID=3
		PSID:27(SIGNED) 80211 X01T Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XMIT Len=279/29 TID=3
		PSID:8007(PLAIN) 80211 XMIT Len=126/118 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) 80211 XHIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XHIT Len+279/29 TID=8
		PSID:27(SIGNED) 80211 X01IT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PCS XMIT Len=279/29 TID=1
		PSID:8007(PLAIN) 80211 X011 Len=126/118 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) 80211 X01T Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PCS XMIT Len=279/29 TID=8
		PSID:27(SIGNED) 80211 XMIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XMIT Len+279/29 TID+3
		PSID:8007(PLAIN) 80211 XMIT Len-126/118 Pow=46 Rate=6000 TID=3
		PSID:8007(PLAIN) 80211 X01T Len=49/41 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) 80211 XMIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XHIT Len=279/29 TID=1
		PSID:27(SIGNED) 88211 XMIT Len=279/29 Pow=46 Rate=6000 FID=3
		PSID:27(SIGNED) PCS XMIT Len=279/29 TID=3
		PSID:8007(PLAIN) 80211 XMIT Len=126/118 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) 80211 XMIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XMIT Len=279/29 TID=3
		PSID:27(SIGNED) 80211 XMIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PC5 XMIT Len=279/29 TID=1
		PSID:8007(PLAIN) 80211 XMIT Len=125/118 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) 80211 XMIT Len=279/29 Pow=46 Rate=6000 TID=3
		PSID:27(SIGNED) PCS XMIT Len=279/29 TID=3
		PSID:27(SIGNED) 80211 XMIT Len=279/29 Pou=46 Rate=6000 TID=3
22:17:13.425	AD:SCH1	PSID:27(SIGNED) PCS XMIT Len=279/29 TID=3





